

THREAD TREATMENT SELECTOR CHART



Threadlockers							Thread Sealants			
Product	Low Strength Threadlocker PURPLE	Medium Strength Threadlocker BLUE	Surface Sensitive BLUE Threadlocker (Preapplied Replacement)	Permanent Strength Threadlocker RED	High Strength Threadlocker RED	Hi-Temp Threadlocker RED (Preapplied Replacement)	Penetrating Grade Threadlocker GREEN (Post Applied)	Pre-Applied Hi-Performance Thread Sealant Replacement Low Odor	Pre-Applied Hi-Temp Thread Sealant Replacement Low Odor	
Sizes Available - Product No.	6 ml - 24024 10 ml - 22210 50 ml - 22250 250 ml - 22225	6 ml - 24200 36 ml - 24240 50 ml - 24250 90 ml - 24283 250 ml - 24225	6 ml - 24027 10 ml - 24300 50 ml - 24350 250 ml - 24325	6 ml - 19962 10 ml - 26210 36 ml - 26240 50 ml - 26250 250 ml - 26225	6 ml - 27100 10 ml - 27110 36 ml - 27140 50 ml - 26150 250 ml - 27125	6 ml - 24026 10 ml - 27200 36 ml - 27240 50 ml - 27250 250 ml - 27225	6 ml - 29000 10 ml - 29010 36 ml - 29040 50 ml - 29050 250 ml - 29025	50 ml - 56521 250 ml - 56525	6 ml - 59214 50 ml - 59235 (formerly 59231) 250 ml - 59225	
Color	Purple	Blue	Blue	Red	Red	Red	Green	White	White	
Fasteners/Fittings	#2 to 1/4" (2.2 - 6mm)	1/4" to 3/4" (6-20mm)	1/4" to 3/4" (6-20mm)	3/8" to 1" (10-25mm)	3/8" to 1" (10-25mm)	5/8" to 1" (16-25mm)	#2 to 1/2" (2.2 - 12mm)	Up to 2" (50mm)	Up to 2" (50mm)	
Torque, in.-lbs.	62/27	115/53	180/62	168/150	168/150	230/225	180/270	NA	NA	
Temperature Range	-65° to 300°F (-54° to 149°C)	-65° to 300°F (-54° to 149°C)	-65° to 300°F (-54° to 149°C)	-65° to 300°F (-54° to 149°C)	-65° to 300°F (-54° to 149°C)	-65° to 450°F (-54° to 232°C)	-65° to 300°F (-54° to 149°C)	-65° to 300°F (-54° to 149°C)	-65° to 300°F (-54° to 149°C)	
Applications	Carburetor relay lock, throttle body assembly, choke assembly, interior panel screws and fuel injection set screws	Valve cover bolts, water pump bolts, oil pan bolts, drive shaft bolts, carburetor studs	Rocker studs, rocker adjustment bolts, disc brake calipers, intakes and alternator and pulley assemblies	Applied before assembly of air tools, cylinder block bolts, ring gear bolts, transmission shaft bolts	Threaded and slip fit joints on cylinder block and rocker arm, transmission and shaft bolts	Camshaft sprocket bolts, crankshaft bolts, idler bearings, ring gear bolts, transmission input and output shaft threads	Pre-assembles fasteners, instrument screws, electrical connectors, carburetors, adjustment screws	Stainless steel fittings, head bolts into through holes, oil PSI sending units/sensors, oil and coolant lines, intake manifold switches, rear axle fill plug, fuel fittings	Head bolts into through holes, oil PSI sending units/sensors, oil and coolant lines, fuel fittings, rear axle fill plug, brake/power steering fittings	
Automotive OEM Interchange	<p>Ford ESE-M492204-A1 WSK-M2G351-A4</p> <p>General Motors 1234 5382 998 5436</p>	<p>Isuzu 1-8844-9032-0 1322 1338 1-8844-9033-0 1324 1364 9-8893-2601-0 0133 9-8893-2605-0 1370-137</p> <p>Mazda 105177743</p> <p>Mercedes-Benz A00398931710011 A00398931710002 A00398931710004 A00398931710005</p> <p>Mitsubishi 3M4177</p> <p>Nissan 999MPAM005</p>	<p>BMW 133789 07-58-9-056-031</p> <p>Ford ESK-M4G-247-A2 WSK-M297351-A2 WSK-M2G351-A7</p> <p>Honda 08718-0009</p> <p>Isuzu JVSCDS0922 JVSCDS0921</p>	<p>Jaguar 1031240 JVS CDS0921</p> <p>Land Rover LRNA-24078</p> <p>Toyota 00001-01003</p>	<p>BMW 81229400086 (Specified as 270)</p> <p>Chrysler 4318032 4057987 MSCD 96-A</p> <p>Ford EOAZ-19554-BA WSK-M2G351-A3 ESEM4148A SEEM4203A2</p> <p>General Motors 998 5300 1773.00000065 9985259</p> <p>Isuzu 1-8844-6373-0 9-8893-2601-0 9-8893-2602-0</p> <p>Jaguar 1120333</p> <p>Land Rover LRNA-21436 (Specified as 270) LRNA-27131</p> <p>Mercedes-Benz A3459890271 A3459890171</p> <p>Nissan 999MPAM004</p>	<p>Chrysler 0 5014205 AA J4570669 8800619 5356 779</p> <p>Daewoo HI-TEMP THREAD SEALANT</p> <p>General Motors 12345493 998 5399</p> <p>Hyundai 272 RED</p> <p>Land Rover LRNA-27240</p>	<p>Nissan 999MPAM004</p> <p>SAAB 0245761</p> <p>Subaru TB1303</p>	<p>Mitsubishi 3M8659 3M8730 3M8731</p> <p>Chrysler 4186369 4187099 MSCC-77</p> <p>Ford SSM-4G-9520-A ESE-M4G203-A1 WSK-M2G351-A1</p> <p>General Motors 998 5306</p> <p>Isuzu 132,013,211,323 1-8844-6375-0 13,311,361</p> <p>Land Rover LRNA-29031</p> <p>Volvo 591264</p> <p>Case B17424</p> <p>Caterpillar 4C9508, 4C9509</p> <p>Cummins 3823682</p> <p>Detroit Diesel 23509539</p>	<p>Chrysler 4187257 MSCD-95B</p> <p>Daewoo High Performance Thread Sealant</p> <p>Ford WSK-M292350-A2 ESE-M492-194-8</p> <p>General Motors 12346004 998 5427</p> <p>Land Rover LRNA-21456</p> <p>Mazda 77-300E-01</p> <p>Mitsubishi 999MPAM002</p> <p>Nissan 999MPA002</p> <p>Saturn 21485278</p>	<p>Chrysler 4318034 4318044 J4570588 2654648 4267247 MSCD-95A</p> <p>Ford D8AZ-19554-A XW7Z-19554-A WSK-M2G350-A2</p> <p>General Motors 105 2080 998 5253 12346004</p> <p>Hyundai 565 WHITE</p> <p>Saturn 21485278</p> <p>John Deere TY9374, TY9375</p> <p>Kenworth 592</p> <p>Mack 5166-59214</p> <p>Case B17503, B17425</p> <p>Caterpillar SP3413</p> <p>Cummins 3375066</p>
*3/8-16 fastener										

To contact Permatex for technical information call toll free: 87-PERMATEX (877-376-2839). Contact your Permatex Distributor Today for Details.

To fax an order: 1-800-432-2067.

Please visit our Web Site www.permatex.com for additional product info.

Permatex, Ultra Blue, Ultra Black, Ultra Copper Ultra Grey, and the Right Stuff are trademarks of Permatex, Inc. ©2003. All rights reserved. 0310-292/PX-0194

Please see reverse side for Gasket Maker and Sealant Selector Chart.